

Product Features

- wetted parts made of stainless steel
- maintenance-free spindle gasket with self-lubricating EPDM lip gasket
- EPDM-seat gasket
- male union thread
- with sidewise drain valve, rotatable hose connection element G 3/4
- with test portcheck valve with SST spring
- Check valve with 551 spring
- wear-resistant stainless steel valve seatwith a black handwheel
- with a black handwhee
- free from dead spotsOpen position indicator
- for any installation position

Standards and Approvals

- according to DVGW regulations
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- acc. to DIN EN 13959 provisions
- ÜA-Reg.-Nr. R-15.2.3-21-17049, WIEN-ZERT

Technical Data

- pressure rating PN 16
- max. operating temperature 110 °C

part no.	DN	A1	A2	D1 (mm)	H1 (mm)	H2 (mm)	L1 (mm)	Zeta	$\Delta p_{opening}$ (hpa)	cv (m³/h)	kg
0601G01500	15	G 3/4	G 1/4	60	100	20,5	70	4,9	120	4,03	0,519
0601G02000	20	G 1	G 1/4	60	120	21	78,5	3,6	110	8,3	0,660
0601G02500	25	G 1 1/4	G 1/4	70	140	23	97	2,9	130	14,6	1,077
0601G03200	32	G 1 1/2	G 1/4	70	165	26	110	2,6	80	25,3	1,315
0601G04000	40	G 1 3/4	G 1/4	90	190	30,5	130	3,1	80	35,9	1,989
0601G05000	50	G 2 3/8	G 1/4	90	230	35	145	2,3	70	64,7	2,851

accessory

SST sampling valve, figure 087 00 insulation shell for inclined stop valves, figure 471 10 gunmetal solder union connector, figure 476 04 gunmetal union connector, union nut, FPT, figure 476 06 gunmetal union connector, union nut, FPT, with drain valve, figure 476 07 gunmetal union connector, union nut, MPT, figure 476 08 solder / pressfit union connector, figure 476 14 pressfit union connector, MAPRESS stainless steel and copper, figure 476 22 pressfit union connector, SANPRESS and PROFIPRESS, figure 476 30 pressfit union connector, MEPLA, figure 476 40 pressfit union connector, MAPRESS stainless steel, figure 476 20

pressfit union connector, SANPRESS INOX, figure 476 70

pressfit union connector for Viega RAXOFIX, figure 476 32