




Product Features

- for hydraulic balancing of hot water return systems (PWH-C)
- wetted parts made of stainless steel
- maintenance-free spindle gasket with self-lubricating EPDM lip gasket
- EPDM-seat gasket
- male union thread
- free from dead spots
- with a black handwheel
- keeps throttle pre-setting when vale is closed and opened
- indication of pre-setting on bracket
- without drain port (drain valve cannot be added)
- Open position indicator
- wear-resistant stainless steel valve seat



Standards and Approvals

- DVGW approval
- SVGW approval
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 2
- DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17049, WIEN-ZERT

Technical Data

- pressure rating PN 16
- max. operating temperature 110 °C

part no.	DN	A1	D1 (mm)	H1 (mm)	H2 (mm)	L1 (mm)	Zeta	cv (m³/h)	kg
0780G01500	15	G 3/4	60	100	17,5	70	2,3	5,9	0,561
0780G02000	20	G 1	60	120	19	78,5	1,6	12,5	0,713
0780G02500	25	G 1 1/4	70	140	21	97	1,4	21,3	1,161
0780G03200	32	G 1 1/2	70	165	24	110	1,1	38,7	1,519

accessory

- insulation shell for inclined stop valves, figure 471 10
- gunmetal solder union connector, figure 476 04
- gunmetal union connector, union nut, FPT, figure 476 06
- gunmetal union connector, union nut, FPT, with drain valve, figure 476 07
- gunmetal union connector, union nut, MPT, figure 476 08
- solder / pressfit union connector, figure 476 14
- pressfit union connector, MAPRESS stainless steel and copper, figure 476 22
- pressfit union connector, SANPRESS and PROFIPRESS, figure 476 30
- pressfit union connector, SANHA and NiroSan, figure 476 35
- pressfit union connector, MEPLA, figure 476 40
- pressfit union connector, MAPRESS stainless steel, figure 476 20
- pressfit union connector, SANPRESS INOX, figure 476 70
- adaptor, double union nut, figure 101 06
- pressfit union connector for Viega RAXOFIX, figure 476 32