



**Product Features**

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- maintenance-free spindle sealing with self-lubricating and under pressure replaceable EPDM-lip gasket
- EPDM-seat gasket
- cone rotatable, protected against water hammer
- female pipe thread
- spindle thread not in contact with medium
- wear-resistant valve seat made of stainless steel up to DN 50
- with a black handwheel
- free from dead spots
- Open position indicator

**Standards and Approvals**

- according to DVGW regulations
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

**Technical Data**

- pressure rating PN 16
- max. operating temperature 110 °C

part no.	DN	A1	D1 (mm)	H1 (mm)	L1 (mm)	T1 (mm)	kg
1830201500	15	Rp 1/2	60	105	62	13,2	0,374
1830202000	20	Rp 3/4	60	115	74	14,5	0,515
1830202500	25	Rp 1	70	140	82	16,8	0,774
1830203200	32	Rp 1 1/4	70	167	98	19,1	1,156
1830204000	40	Rp 1 1/2	90	170	105	19,1	1,418
1830205000	50	Rp 2	90	202	125	23,4	2,148