




Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- 10 year warranty
- maintenance-free spindle sealing with self-lubricating and under pressure replaceable EPDM-lip gasket
- EPDM-seat gasket
- cone rotatable, protected against water hammer
- press connection for Geberit MEPLA pipe
- with plugged drain port
- Pt1000 temperature sensor or thermometer can be added using immersion sleeve
- spindle thread not in contact with medium
- wear-resistant stainless steel valve seat
- with a black handwheel
- free from dead spots
- Open position indicator



Standards and Approvals

- DVGW approval
- ÖVGW approval
- SVGW approval
- KIWA approval
- VA approval
- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 1213
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical Data

- pressure rating PN 16
- max. operating temperature 110 °C

part no.	DN	da x s	A1 (mm)	A2	D1 (mm)	H1 (mm)	L1 (mm)	T1 (mm)	Zeta	cv (m³/h)	kg
1904001600	15	16 x 2,25	11,5	G 1/4	60	90	122	25,5	2,3	5,9	0,404
1904002000	15	20 x 2,5	15	G 1/4	60	90	126,5	27	1,6	12,5	0,423
1904002600	20	26 x 3,0	20	G 1/4	60	105	146,5	31,5	1,6	12,5	0,551
1904003200	25	32 x 3,0	26	G 1/4	70	132	154	28	1,1	38,7	0,864
1904004000	32	40 x 3,5	33	G 1/4	70	154	185,5	33,5	1,8	47,2	1,313
1904005000	40	50 x 4,0	42	G 1/4	70	162	196	37,5	1,8	47,2	1,749

accessory

- gunmetal sampling valve, figure 187 00
- insulation shell for inclined stop valves, figure 471 10
- drain valve made of gunmetal/plastic, figure J7109 173 00
- extension element for drain valve DN 8, figure J6109 473 00
- axial drain valve and immersion sleeve, figure J7109 150 00
- Pt 1000 temperature sensor, figure T5100 140 00
- dial thermometer, figure T5100 150 00