

Y-strainer, figure 605 00





Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- easily replaceable double mesh made of stainless steel
- flange connection
- for any installation position

Standards and Approvals

- according to accepted materials list from German environmental agency
- DIN EN 558-1
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical Data

- pressure rating PN 16
- max. operating temperature 200 °C
- mesh width outer supporting sieve 0.6 mm
- mesh width inner screen 0.3 mm

part no.	DN	bolt holes	D1 (mm)	D2 (mm)	D3 (mm)	H1 (mm)	L1 (mm)	S1 (mm)	SW1 (mm)	Zeta	cv (m^3/h)	kg
6050005000	50	4	165	102	50	91	230	14	50	4,4	47,1	5,876
6050006500	65	4	185	122	65	101	290	15	60	4,2	81,6	8,646
6050008000	80	8	200	138	80	112	310	16	60	3,9	128	10,697
6050010000	100	8	220	158	100	151	350	18	70			16,85

accessory

backing ring for stub flange, figure 410 00
stub flange, figure 425 00
threaded flange, figure 426 00
gasket, figure 428 00

 © Copyright by Gebr. Kemper GmbH + Co. KG / Harkortstraße 5 / D-57462 Olpe