



Product Features

- as an automatic circulation balancing valve
- thermostatic balancing valve for cold water return branches with kv-min ≥ 0.03
- for thermostatic, hydraulic balancing
- thermostatic balancing unit
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- maintenance-free EPDM spindle seal
- PTFE seat gasket
- free from dead spots
- with isolating, balancing and pre-setting function
- male union thread

Standards and Approvals

- plastic parts with KTW and W 270 approval
- according to accepted materials list from German environmental agency
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical Data

- control range 15 °C - 22 °C
- pressure rating PN 10
- max. operating temperature 50 °C
- max. ambient temperature 50 °C

part no.	DN	A1	D1 (mm)	H1 (mm)	H2 (mm)	L1 (mm)	T1 (mm)	cv min (m³/h)	cv (m³/h)	kg
6170G01500	15	G 3/4	33,7	91,5	37,8	73	31	0,03	1,8	0,476

accessory

- pressfit union connector, MAPRESS stainless steel and copper, figure 476 22
- pressfit union connector, SANPRESS and PROFIPRESS, figure 476 30
- pressfit union connector, SANHA and NiroSan, figure 476 35
- pressfit union connector, MEPLA, figure 476 40
- pressfit union connector, MAPRESS stainless steel, figure 476 20
- pressfit union connector, SANPRESS INOX, figure 476 70
- pressfit union connector for Viega RAXOFIX, figure 476 32
- insulation shell for KHS CoolFlow cold water balancing valve, figure 471 27