



Product Features

- consisting of FROSTI®-PLUS frost-proof outdoor valve figure 574 00 and KHS floor box figure 640 50
- wetted metal parts made of dezincification-free and corrosion-resistant gunmetal (in closed position), resistant against aggressive water
- prevents stagnation in ring pipe installations through forced flow during downstream withdrawals, can be used in cold drinking water (PWC)
- venturi technology creates parallel flow through main and loop pipe
- KHS Flow-Splitter pass with female thread
- plumbing unit return pipe with female thread
- plumbing unit feed pipe with female thread
- free from dead spots
- KHS Flow-Splitter - static integrated into insulation shell of Neopor®

Standards and Approvals

- FROSTI with DVGW, SVGW, ÖVGW, KIWA, BELGAQUA and VA approvals
- plastic parts with KTW and W 270 approval
- according to UBA valuation basis
- soundproofing certification according to DIN EN ISO 3822 Class 1
- building material class B1 according to DIN 4102
- EN 1717

Technical Data

- pressure rating PN 16

part no.	DN	A1	A2	A3	H1 (mm)	H2 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	T1 (mm)	kg
6406001500	15	Rp 1/2	Rp 1/2	Rp 1/2	110	48,5	210	185	100	40	2,47
6406002000	20	Rp 3/4	Rp 1/2	Rp 1/2	110	58,5	210	185	100	50	2,64

accessory

- socket key operated for FROSTI®, figure 574 00 001
- operating handle for FROSTI®, lockable, figure 575 00 003
- operating handle for FROSTI®, lockable and with master key system, figure 575 02 003
- extension for FROSTI®-PLUS, figure 574 00 002
- fixing set for FROSTI®-PLUS, figure 574 00 005
- dismantling key for lockable operating handle, figure 575 01 003
- sealing collar for FROSTI®, figure 574 00 006