



Product Features

- for temperature controlled operation of the KHS HS2® hygiene-flushing box
- to be connected to KHS HS2® hygiene-flushing box
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- male union thread
- free from dead spots

Standards and Approvals

- according to accepted materials list from German environmental agency
- DIN EN 60751
- ÚA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical Data

- pressure rating PN 16
- max. operating temperature 105 °C
- length of connection cable 5 m

part no.	DN	A1	A2	A3	H1 (mm)	L1 (mm)	L2 (mm)	kg
6890001500	15	G 3/4	G 3/4	G 1/4	65	65	60	0,488
6890002000	20	G 1	G 1	G 1/4	68	67	60	0,549
6890002500	25	G 1 1/4	G 1 1/4	G 1/4	70,5	72	70	0,702
6890003200	32	G 1 1/2	G 1 1/2	G 1/4	78	77	80	0,772
6890004000	40	G 1 3/4	G 1 3/4	G 1/4	79	82	80	0,871
6890005000	50	G 2 3/8	G 2 3/8	G 1/4	88,5	90	80	1,294

accessory

- insulation shell for MULTI T-PIECE, figure 471 28
- gunmetal solder union connector, figure 476 04
- gunmetal union connector, union nut, FPT, figure 476 06
- gunmetal union connector, union nut, FPT, with drain valve, figure 476 07
- gunmetal union connector, union nut, MPT, figure 476 08
- solder / pressfit union connector, figure 476 14
- pressfit union connector, MAPRESS stainless steel and copper, figure 476 22
- pressfit union connector, SANPRESS and PROFIPRESS, figure 476 30
- pressfit union connector, SANHA and NiroSan, figure 476 35
- pressfit union connector, MEPLA, figure 476 40
- pressfit union connector, MAPRESS stainless steel, figure 476 20
- pressfit union connector, SANPRESS INOX, figure 476 70
- pressfit union connector for Viega RAXOFIX, figure 476 32